



Static earth lead and plier clamp

| Description | Cable length (max) | Weight each | Part No. |
|-----------------------------------|--------------------|-------------|--------------|
| Static earth lead and plier clamp | 3 metres | 0.56kg | SK010 |

Clamp certification II 1GD T6 Approved

A multicored high-tensile steel cable with a medium duty hard anodized diecast aluminium clamp. The Cen-Stat™ cable has an orange Hytrel coating and is pre-terminated with an M10 compression ring terminal. The clamp has stainless steel contact teeth.



Static earth lead and heavy duty clamp

| Description | Cable length (max) | Weight each | Part No. |
|--|--------------------|-------------|--------------|
| Static earth lead and heavy duty clamp | 5 metres | 1.09kg | SK020 |

Clamp certification II 1GD T6

A multicored high-tensile steel cable with a heavy duty passivated carbon steel clamp. The Cen-Stat™ cable has an orange Hytrel coating and is pre-terminated with an M10 compression ring terminal. The clamp has twin tungsten carbide contact teeth.



Static discharge reel and plier clamp

| Description | Cable length (max) | Weight each | Part No. |
|---------------------------------------|--------------------|-------------|--------------|
| Static discharge reel and plier clamp | 6.1 metres | 4kg | SK030 |

Clamp certification II 1GD T6. Reel certification II 2GD T6

A multicored galvanised steel cable with a medium duty hard anodized diecast aluminium clamp. The cable is housed in a self-retracting cable drum with an instant lock mechanism. The clamp has stainless steel contact teeth.



Static discharge reel and heavy duty clamp

| Description | Cable length (max) | Weight each | Part No. |
|--|--------------------|-------------|--------------|
| Static discharge reel and heavy duty clamp | 15.2 metres | 5.9kg | SK040 |

Clamp certification II 1GD T6. Reel certification II 2GD T6

A multicored galvanised steel cable with a heavy duty passivated carbon steel clamp. The cable is housed in a self-retracting cable drum with an instant lock mechanism. The clamp has twin tungsten carbide contact teeth.